

## EDL-250/SW - PA Loudspeaker



Weatherproof PA sound projector

- 100 V transmission technology
- Weatherproof plastic housing
- Connection cable with 3 power taps
- Pivoting mounting bracket

## Tekniske data

|                                |                        |
|--------------------------------|------------------------|
| Active/passive                 | : passive              |
| Transmission technology        | : 100 V                |
| Total output power             | : -                    |
| Power rating (RMS)             | : -                    |
| Total power rating             | : -                    |
| Power rating (RMS)             | : 30/15/7.5 W          |
| Impedance                      | : -                    |
| Frequency range                | : 125-15,000 Hz        |
| THD                            | : -                    |
| S/N ratio                      | : -                    |
| Input signal                   | : -                    |
| System                         | : -                    |
| Full range speaker             | : -                    |
| Bass speaker                   | : -                    |
| Midrange speaker               | : -                    |
| Tweeter                        | : -                    |
| Number of speakers             | : -                    |
| Speaker size                   | : -                    |
| SPL                            | : 101 dB/W/m           |
| Max. rated SPL                 | : -                    |
| Beam angle                     | : -                    |
| Radiation angle, horizontal    | : -                    |
| Radiation angle, vertical      | : -                    |
| Features                       | : -                    |
| Housing material               | : plastic              |
| Colour                         | : black                |
| Mounting device                | : mounting bracket     |
| Protected against ball rebound | : -                    |
| Protection class               | : IP44                 |
| Admiss. ambient temp.          | : 0-40 °C              |
| Power supply                   | : -                    |
| Dimensions                     | : Å~ 180Å mm x 200Å mm |
| Width                          | : Å~ 180 mm            |
| Height                         | : -                    |
| Depth                          | : 200 mm               |



|                                |                        |
|--------------------------------|------------------------|
| Weight                         | : 2.1 kg               |
| Inputs                         | : -                    |
| Outputs                        | : -                    |
| Replacement voice coil         | : -                    |
| Other features                 | : -                    |
| Accessories                    | : -                    |
| Packing dimensions (W x H x L) | : 0.23 x 0.26 x 0.24 m |
| Gross weight                   | : 2.44 kg              |
| Net weight                     | : 2.116 kg             |