

KU-916T - Horn Driver



Weatherproof horn driver

- 100 V line technique
- Protected against powerful water jets
- Power selector switch
- 3.5 cm (1.4") mounting flange
- 60 cm connection cable

Tekniske data

| | |
|--------------------------------|--------------------------|
| Active/passive | : passive |
| Transmission method | : 100 V |
| Total output power | : - |
| Power rating (RMS) | : - |
| Total power rating | : 60 W |
| Power rating (RMS) | : 60/50/40/30/20/10 W |
| Impedance | : - |
| Frequency range | : 160-7,000 Hz |
| THD | : - |
| S/N ratio | : - |
| Input signal | : - |
| System | : - |
| Full range speaker | : - |
| Bass speaker | : - |
| Midrange speaker | : - |
| Tweeter | : - |
| Number of speakers | : 1 |
| Speaker size | : - |
| Sensitivity | : 113 dB/W/m |
| Max. rated SPL | : - |
| Radiation angle, horizontal | : - |
| Radiation angle, vertical | : - |
| Features | : power selector switch |
| Housing material | : metal |
| Colour | : dark grey |
| Mounting device | : 3.5 cm mounting flange |
| Protected against ball rebound | : - |
| Protection class | : IP66 |
| Admiss. ambient temp. | : -20 °C to +50 °C |
| Power supply | : - |
| Dimensions | : 150 mm x 158 mm |
| Width | : 150 mm |
| Height | : - |
| Depth | : 158 mm |
| Weight | : 2.75 kg |



| | |
|------------------------|----------------|
| Inputs | : - |
| Outputs | : - |
| Replacement voice coil | : KU-916T/VC |
| Other features | : weatherproof |
| Accessories | : - |