

## WALL-06SET/WS - Active Cabinets



Active 2-way stereo speaker system, 2 x 30 W

- Set consists of one active and one passive speaker system. Connection of the passive system to the active system via screw terminal strip
- Active speaker system with integrated 2-channel amplifier
- Stereo RCA input or balanced input L/R via screw terminal strip
- Volume control and 2-way tone control
- Auto standby
- Built-in power supply with 3-pin IEC jack
- 16 cm (6") bass speaker system and dome tweeter
- Stylish white plastic cabinet
- Mounting bracket for pivoting and tilting

Active 2-way stereo speaker system, 2 x 30 W

- Set consists of one active and one passive speaker system. Connection of the passive system to the active system via screw terminal strip
- Active speaker system with integrated 2-channel amplifier
- Stereo RCA input or balanced input L/R via screw terminal strip
- Volume control and 2-way tone control
- Auto standby
- Built-in power supply with 3-pin IEC jack

- 16 cm (6") bass speaker system and dome tweeter
- Mounting bracket for pivoting and tilting

## Tekniske data

|                                |  |
|--------------------------------|--|
| Active/passive                 | : active/passive                                   |
| Transmission method            | : cable  |
| Total output power             | : 2 x 50 W   |
| Power rating (RMS)             | : 2 x 30 W   |
| Total power rating             | : -  |
| Power rating (RMS)             | : -  |
| Impedance                      | : -  |
| Frequency range                | : 70-20,000 Hz                                     |
| THD                            | : -  |
| S/N ratio                      | : -  |
| Input signal                   | : 890 mV/20 kOhm (unbal,.) 1,600 mV/40 kOhm (bal.) |
| System                         | : 2-way  |
| Full range speaker             | : -  |
| Bass speaker                   | : 16 cm (6") bass speaker                          |
| Midrange speaker               | : -  |
| Tweeter                        | : dome tweeter                                     |
| Number of speakers             | : 2  |
| Speaker size                   | : 16 cm (6")                                       |
| Sensitivity                    | : 90 dB/W/m  |
| Max. rated SPL                 | : 105 dB   |
| Radiation angle, horizontal    | : -  |
| Radiation angle, vertical      | : -  |
| Features                       | : -  |
| Housing material               | : plastic  |
| Colour                         | : white  |
| Mounting device                | : mounting bracket                                 |
| Protected against ball rebound | : -  |
| Protection class               | : -  |
| Admiss. ambient temp.          | : 0-40 °C  |
| Power supply                   | : &acd; 230V/50 Hz/140VA                           |
| Dimensions                     | : 196 x 303 x 250Å mm (with bracket)               |
| Width                          | : 196 mm   |
| Height                         | : 303 mm   |
| Depth                          | : 250 mm   |
| Weight                         | : 8Å kg (pair)                                     |



|                        |  |
|------------------------|--|
| Inputs                 | : 1 x RCA L/R (unbalanced)<br>1 x terminal L/R (balanced)<br>spr.-load. speak. term. (passive speaker system)<br>spr. load. speak. term. |
| Outputs                | : -  |
| Replacement voice coil | : -  |
| Other features         | : pair   |
| Accessories            | : -  |