

ESUB-8F/WS - Active Subwoofer



Active subwoofer system, 50 W

- Compact active subwoofer of elegant design as an addition to compact speakers for hi-fi, PA, home cinema and home recording
- Beside volume control, a phase switch and an automatic switch-on, the amplifier also features an adjustable crossover frequency (50-250 Hz)
- High-quality bass-reflex MDF cabinet, high-gloss white
- 20 cm (8") bass speaker
- Inputs via 1 x RCA L/R or screw terminals for high-level L/R
- Parallel line out RCA L/R
- Additional outputs high-level L/R for mid-high range speakers. Thus, well suited for connection to already existing speaker lines
- White fabric front cover

Tekniske data

Active/passive	: active
Transmission method	: -
Total output power	: 90 W
Power rating (RMS)	: 50 W
Total power rating	: -
Power rating (RMS)	: -
Impedance	: -
Frequency range	: 30-250 Hz
THD	: -
S/N ratio	: -
Input signal	: 185 mV/9 kOhm (RCA L/R) 4 V/480 Ohm (high IN)
System	: -
Full range speaker	: -
Bass speaker	: 20 cm (8") bass speaker
Midrange speaker	: -
Tweeter	: -
Number of speakers	: 1
Speaker size	: 20 cm (8")
Sensitivity	: 87 dB/W/m
Max. rated SPL	: 105 dB
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Features	: -
Housing material	: wood
Colour	: white, high-gloss
Mounting device	: -
Protected against ball rebound	: -
Protection class	: -
Admiss. ambient temp.	: 0-40 °C
Power supply	: ∿ 230 V/50 Hz/152 VA
Dimensions	: 300 x 330 x 340 mm
Width	: 300 mm
Height	: 330 mm
Depth	: 340 mm
Weight	: 9.8 kg



Inputs	: 1 x RCA (L/R), unbal., IN 1 x screw terminals (stereo), high-level IN
Outputs	: 1 x RCA (L/R) 1 x screw terminals (stereo), high-level OUT
Replacement voice coil	: -
Other features	: -
Accessories	: -