

## HSE-152/SK - Headworn Microphone



### Ultra-light headband microphone

The reliable HSE-150 is now also available with cardioid polar pattern. Thus, the extensive list of features of the HSE-150 is now completed by a further important detail: excellent feedback rejection. This microphone also features a high-quality back electret cartridge which provides an optimum sound. The extra lightweight and almost invisible ergonomic headband makes the HSE-152 a perfect tool for every vocal artist.

- Wide transmission range
- Excellent feedback rejection
- Very comfortable to wear
- Stable positioning
- Turning cartridge arm of adjustable length
- Drip ring (protects cartridge from moisture)
- Compatible with all pocket transmitters TXS-...HSE with 3-pole mini XLR connection
- External power supply, e.g. via phantom power supply adapter EMA-1, EMA-2, EMA-40 or EMA-300P
- Microphone windshield

### Ultra-light headband microphone

- Cardioid polar pattern
- High-quality back electret cartridge
- 3-pole mini XLR connection
- Excellent feedback rejection
- Turning cartridge arm of adjustable length
- Drip ring (protects cartridge from moisture)
- Compatible with all pocket transmitters TXS-...HSE with 3-pole mini XLR connection
- External power supply, e.g. via phantom power supply adapter EMA-1 or EMA-300P

- Microphone windshield

## Tekniske data

Description	: headband microphone
Version	: -
Transmission method	: cable
Polar pattern	: cardioid
System	: back electret
Carrier frequency range	: -
Transmitting power	: -
Power supply	: -
Operating time	: -
Audio frequency range	: 20-20,000 Hz
Nominal impedance	: 1.5 kOhm
Sensitivity	: 1.8 mV/Pa
S/N ratio	: -
Max. sound pressure	: 130 dB
Power supply	: DC 1.5-9 V
Gooseneck length	: -
Housing material	: -
Admiss. ambient temp.	: 0-40 °C
Dimensions	: -
Weight	: 7 g
Cable	: -
Connection	: 3-pole mini XLR