

HSE-821SX - Headworn Microphone



Replacement electret headband microphone

- Suitable for vocal and speech applications
- Microphone cartridge with cardioid polar pattern
- Gooseneck cartridge arm
- 1.3 m connection cable with 3.5 mm plug, with latching device
- Operation via a pocket transmitter of the series TXS-820SX, TXS-822SX, TXS-820LT or TXS-822LT
- Microphone windshield

Tekniske data

| | |
|-------------------------|-----------------------|
| Description | : headband microphone |
| Version | : - |
| Transmission method | : cable |
| Polar pattern | : cardioid |
| System | : electret |
| Carrier frequency range | : - |
| Transmitting power | : - |
| Power supply | : - |
| Operating time | : - |
| Audio frequency range | : 80-12,000 Hz |
| Nominal impedance | : 680 Ohm |
| Sensitivity | : 5.6 mV/Pa |
| S/N ratio | : 60 dB |
| Max. sound pressure | : 110 dB |
| Power supply | : 1.5-3 V |
| Gooseneck length | : - |
| Housing material | : - |
| Admiss. ambient temp. | : 0-40 °C |
| Dimensions | : - |
| Weight | : 60 g |
| Cable | : 1.3 m |
| Connection | : 3.5 mm plug |