

## HSE-110 - Headworn Microphone



Umbau von 4-Pol-HSE-Kopfbügelmikrofonen zum Anschluss an JTS-Taschensender  
 Reconfiguration of 4-pole HSE headband mics for the connection to JTS pocket transmitters



### Headband microphone

- High-quality back electret cartridge
- Very linear frequency response, especially resistant to external sound due to its supercardioid characteristic with high back suppression
- The power supply adapter EMA-1 or a respective power supply is required for operation
- 3-pole mini XLR inline jack, matching EMA-1 or a pocket transmitter TXS-...HSE

## Tekniske data

Description	: headband microphone
Version	: -
Transmission method	: cable
Polar pattern	: supercardioid
System	: back electret
Carrier frequency range	: -
Transmitting power	: -
Power supply	: -
Operating time	: -
Audio frequency range	: 20-20,000 Hz
Nominal impedance	: 3 kOhm
Sensitivity	: 7 mV/Pa
S/N ratio	: -
Max. sound pressure	: 120 dB
Power supply	: DC 1.3-20 V
Gooseneck length	: -
Housing material	: -
Admiss. ambient temp.	: 0-40 °C
Dimensions	: -
Weight	: 69 g
Cable	: -
Connection	: 3-pole mini XLR