

PA-6240 - PA Amplifier



6-zone mono PA mixing amplifier

- 1 x 240 W
- 6 zones, can be controlled individually
- Chime, continuous sound and wailing sound, automatic mute, 2-tone chime or 4-tone chime (selectable)
- Bass, treble and master controls, level display via LEDs, regulated fan
- Insertions for various functions are available at option
- 17 V phantom power for electret microphones
- Connection for zone paging microphone PA-6000RC
- 1 insertion compartment at the front for automatic alarm message insertion PA-1120DMT, a tuner insertion or a CD player insertion, all available at option
- 3 insertion facilities on the rear panel for optional modules with the following features:
 - PA-6FD: fault detection
 - PA-6FD: fault monitoring
 - PA-6FR: anti-feedback

- Mains operation and 24 V emergency power operation
- Removable mounting brackets

Tekniske data

Peak output power	: 340 W
Power rating	: 240 W
Power rating at 2 Ohm	: -
Power rating at 4 Ohm	: -
Power rating at 8 Ohm	: -
Power rating at 16 Ohm	: -
Power rating at 100 V	: -
Power rating with 4 Ohm	: -
bridged operation	
Power rating with 8 Ohm	: -
bridged operation	
Output impedance	: -
Channels	: 5
Zones	: 6
Inputs	: 2.5 mV/5 kOhm, 0.3 V/5 kOhm (mic/line), 0.3 V/15 kOhm (line), 0,775 V/10 kOhm (preamplifier)
Attenuation factor	: -
Frequency range	: 55-16,000 Hz
Crossover network	: -
Crossover frequency	: -
Integrated limiter	: -
Equalizer bass	: ± 10 dB/100 Hz
Equalizer midrange	: -
Equalizer treble	: ± 10 dB/10 kHz
S/N ratio	: ? 70 dBA (mic), ? 80 dBA (line)
Crosstalk attenuation	: -
THD	: < 1%
Mains voltage	: \sim 230 V
Mains frequency	: 50 Hz
Power consumption, operation	: 750 VA
Power consumption, standby	: -
Standby current	: -
Operating voltage (possible alternative)	: DC 24 V
Power supply (possible alternative)	: DC 20 A
Admiss. ambient temp.	: 0-40 °C

Width : 430 mm
Height : 133 mm
Depth : 352 mm



Rack spaces, RS	: 3
Weight	: 15 kg
Connections	: 3 x combo 6.3 mm/XLR (mic/line), 2 x RCA L/R (line), 1 x 6.3 mm jack (preamplifier), 1 x RJ45 (push-to-talk mic), screw terminals (telephone system), screw terminals (speakers), 1 x 6.3 mm jack (ext. amplifier), 1 x RCA