

## AKB-60 - Amplifier Module

60  
W<sub>RMS</sub>



Active speaker module, mono, 45 W at 4 Ohm

- Active module for activating passive speakers
- For mounting e.g. to the rear side of passive speakers
- Line input via XLR or RCA
- Adjustable master output
- Very well-suited as a measuring amplifier of acoustic analysers
- Fanless concept with large heat sink

## Tekniske data

Peak output power	: 60 W
Power rating	: 45 W
Power rating at 2 Ohm	: -
Power rating at 4 Ohm	: 45 W
Power rating at 8 Ohm	: 30 W
Power rating at 16 Ohm	: -
Power rating at 100 V	: -
Power rating with 4 Ohm	: -
bridged operation	
Power rating with 8 Ohm	: -
bridged operation	
Output impedance	: -
Channels	: 1
Zones	: -
Inputs	: 0.4 V/20 kOhm bal., 11 kOhm unbal.
Attenuation factor	: -
Frequency range	: 15-50,000 Hz
Crossover network	: -
Crossover frequency	: -
Integrated limiter	: -
Equalizer bass	: -
Equalizer midrange	: -
Equalizer treble	: -
S/N ratio	: ? 80 dB
Crosstalk attenuation	: -
THD	: < 0.01%
Mains voltage	: ~ 230 V
Mains frequency	: 50 Hz
Power consumption, operation	: 90 VA
Power consumption, standby	: -
Standby current	: -
Operating voltage (possible alternative)	: -
Power supply (possible alternative)	: -
Admiss. ambient temp.	: 0-40 °C
Width	: 212 mm
Height	: 52 mm
Depth	: 190 mm



Rack spaces, RS	: -
Weight	: 2.2 kg
Connections	: 1 x XLR input, bal., 1 x RCA L/R (input), speaker cable for connecting 4-8Ω Ohmspeaker systems