

TXS-812SET - Wireless Microphone



Wireless 2-channel microphone system

- 2 microphone transmitters, 1 receiver, 1 plug-in power supply
- Two-channel UHF version (non-diversity) with channel mixing function which can additionally be selected
- Volume and squelch controls for each channel
- Each channel with LEDs for indicating RF signal and audio signal

Licence-free in the EU.

Tekniske data

General information

| | |
|-------------------------|------------------------------|
| | : - |
| Description | : wireless microphone system |
| Carrier frequency range | : 863.80 MHz , 864.20 MHz |
| Audio frequency range | : 40-15,000 Hz |
| Channels | : 2 |
| THD | : < 0.5% |
| Dynamic range | : ? 90 dB |
| RF S/N ratio | : ? 80 dB |
| Operating time | : - |
| Admiss. ambient temp. | : 0-40 °C |
| Power supply | : - |
| Dimensions | : - |
| Total weight | : - |
| Connections | : - |

Specifications transmitter

| | |
|--------------------------|--|
| | : - |
| Transmitting power | : < 10 mW |
| Operating range | : approx. 30 m |
| Power supply transmitter | : 2 x 1.5 V batt. AA size (not supplied) |

| | |
|-------------------------|----------|
| Width transmitter | : 52 mm |
| Height transmitter | : 52 mm |
| Depth transmitter | : 260 mm |
| Weight transmitter | : 240 g |
| Connections transmitter | : - |

Specifications receiver

| | |
|-----------------------|---|
| | : - |
| Audio signal receiver | : 0-200 mV/10 kOhm (jack)0-400 mV/10 kOhm (XLR, bal.) |
| Power supply receiver | : via encl. plug-in power supply |
| Width receiver | : 210 mm |
| Height receiver | : 46 mm |
| Depth receiver | : 190 mm |
| Weight receiver | : 560 g |
| Connections receiver | : 2 x XLR, bal.1 x 6.3 mm jack, unbal. |