

## SA-100 - Amplifier

2x50  
W<sub>RMS</sub>



Compact universal stereo amplifier, 50 W

- Silent operation due to fanless cooling concept
- Additional 3.5 mm connection with switchable sensitivity on the front panel
- USB port on the front panel for power supply and for charging external devices
- Audio source selector switch
- Controls for volume, bass and treble
- 6.3 mm headphone output
- Robust metal housing

## Tekniske data

|  |   |
|--|---|
| Peak output power                        | : 2 x 50 W  |
| Power rating                             | : 50 W  |
| Power rating at 2 Ohm                    | : -   |
| Power rating at 4 Ohm                    | : 2 x 25 W  |
| Power rating at 8 Ohm                    | : 2 x 20 W  |
| Power rating at 16 Ohm                   | : -   |
| Power rating at 100 V                    | : -   |
| Power rating with 4 Ohm                  | : -   |
| bridged operation                        |   |
| Power rating with 8 Ohm                  | : -   |
| bridged operation                        |   |
| Output impedance                         | : -   |
| Channels                                 | : 2   |
| Zones                                    | : -   |
| Inputs                                   | : 140 mV/46 kOhm (PC, CD, aux) 140 mV/12 kOhm, 25 mV/32 kOhm (player) |
| Attenuation factor                       | : -   |
| Frequency range                          | : 20-20,000 Hz  |
| Crossover network                        | : -   |
| Crossover frequency                      | : -   |
| Integrated limiter                       | : -   |
| Equalizer bass                           | : $\pm 12$ dB   |
| Equalizer midrange                       | : -   |
| Equalizer treble                         | : $\pm 12$ dB   |
| S/N ratio                                | : ? 70 dB   |
| Crosstalk attenuation                    | : -   |
| THD                                      | : -   |
| Mains voltage                            | : $\sim$ 230 V  |
| Mains frequency                          | : 50 Hz   |
| Power consumption, operation             | : 150 VA  |
| Power consumption, standby               | : -   |
| Standby current                          | : -   |
| Operating voltage (possible alternative) | : -   |
| Power supply (possible alternative)      | : -   |
| Admiss. ambient temp.                    | : 0-40 °C   |
| Width                                    | : 212 mm  |
| Height                                   | : 56 mm   |

Depth

: 250 mm





|                 |  |
|-----------------|--|
| Rack spaces, RS | : -  |
| Weight          | : 2.6 kg   |
| Connections     | : 1 x RCA L/R (PC), 1 x RCA L/R (CD), 1 x RCA L/R (aux), 1 x 3.5 mm jack (player), 4 x spring-load. speaker term. (speakers) |