


SA-50 - Amplifier

2 x 25
W MAX



Compact universal stereo amplifier, 25 W

- Silent operation due to fanless cooling concept
- Additional 3.5 mm connection with switchable sensitivity on the front panel
- Audio source selector switch
- Controls for volume, bass and treble
- 6.3 mm headphone output
- Robust metal housing

Tekniske data

Peak output power	: 2 x 25 W
Power rating	: 25 W
Power rating at 2 Ohm	: -
Power rating at 4 Ohm	: 2 x 12.5 W
Power rating at 8 Ohm	: 2 x 10 W
Power rating at 16 Ohm	: -
Power rating at 100 V	: -
Power rating with 4 Ohm bridged operation	: -
Power rating with 8 Ohm bridged operation	: -
Output impedance	: -
Channels	: 2
Zones	: -
Inputs	: 115Â mV/12Â kOhm (PC), 115Â mV/12Â kOhm (CD), 115Â mV/12Â kOhm (aux), 115Â mV/12Â kOhm (player, high), 20Â mV/32Â kOhm (player, low)
Attenuation factor	: -
Frequency range	: 20-20,000 Hz
Crossover network	: -
Crossover frequency	: -
Integrated limiter	: -
Equalizer bass	: ± 12 dB
Equalizer midrange	: -
Equalizer treble	: ± 12 dB
S/N ratio	: ? 65 dB
Crosstalk attenuation	: -
THD	: -
Mains voltage	: \sim 230 V
Mains frequency	: 50 Hz
Power consumption, operation	: 50 VA
Power consumption, standby	: -
Standby current	: -
Operating voltage (possible alternative)	: -
Power supply (possible alternative)	: -

Admiss. ambient temp.

: 0-40 °C

Width

: 212 mm

Height

: 56 mm

Depth

: 200 mm





Rack spaces, RS	: -
Weight	: 1.8 kg
Connections	: 1 x RCA L/R (PC), 1 x RCA L/R (CD), 1 x RCA L/R (aux), 1 x 3.5 mm jack (player), 4 x spring-load. speaker term. (speakers)