

CRB-165CP - Car Speaker Pair



Chassis Speakers for Car Hi-fi Applications

With high-quality carbon fibre cone in a robust standard basket. This speaker impresses by a bass reproduction of amazingly low fundamental resonance which makes it an ideal replacement for original equipment. The sound can be improved considerably without necessarily having to use subwoofers and power amplifiers. An efficient application in more complex car hi-fi systems of high power capability is also possible, of course.

Pair of car chassis speakers, 50 W, 4 Ohm

- 2-way coaxial version
- Carbon fibre cone
- Voice coil of long excursion
- Frequency range: 50-22,000 Hz
- Mounting dim.: Ø 144 mm x 59 mm
- Outside dimensions: Ø 165 mm
- Type 165

Tekniske data

Impedance (Z)	: 4 Ohm
Transmission method	: -
Frequency range	: 50-22,000 Hz
Resonant frequency (fs)	: -
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	: -
Power rating (RMS)	: 50 W
Peak music power output (MAX)	: 100 W
Sensitivity	: 89 dB/W/m
Max. rated SPL	: -
Max. voltage	: -
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Suspension compl. (Cms)	: -
Moving mass (Mms)	: -
Mech. Q factor (Qms)	: -
Electr. Q factor (Qes)	: -
Total Q factor (Qts)	: -
Equivalent volume (Vas)	: -
DC resistance (Re)	: -
Force factor (BxL)	: -
Voice coil induct. (Le)	: -
Voice coil diameter	: -
Voice coil former	: -
Linear excursion (X _{MAX})	: -
Eff. cone area (Sd)	: -
Magnet weight	: 280 g
Magnet diameter	: Å~ 80 mm
Mounting cutout	: Å~ 144 mm
Mounting depth	: 59 mm
Mounting hole diameter	: -
Hole spacing X-axis	: -
Hole spacing Y-axis	: -
Dimensions	: Å~ 165 mm
Outside diameter	: Å~ 165 mm
Width	: Å~ 165 mm



Height	: -
Depth	: -
Protective class	: -
Admiss. ambient temp.	: 0-40 °C
Weight	: 1.68Â kg (pair)
Packing unit	: 2
Type of speaker	: 165