

BC-4000L - Lead-Battery Charger max. 4A

IP65



Charger for rech. lead batteries, 6 V, 12 V, 4 A max.

- For motor vehicles and boats
- Protected against short circuit, reverse polarity and overload
- Trickle charge
- LEDs for indicating charging status, polarity and faulty battery
- 1.8 m connection cable with battery clamps

Tekniske data

| | |
|-----------------------------|--|
| Category | : charger |
| Input voltage | : \approx 230 V/50 Hz/600 mA |
| Output voltage | : DC 7.3/14.4/14.7 V |
| Charging/output current | : 6 V/0.8 A, 12 V/4 A max. |
| Charging time | : dep. on capacity and charging status |
| Trickle charge | : 50-150 mA |
| Polarity selection | : - |
| Switchable output voltage | : - |
| Reactivation | : - |
| Connections | : battery clamps |
| Cable length | : 1.8 m |
| Short-circuit protection | : yes |
| Overload protection | : yes |
| Overheat protection | : - |
| Reverse polarity protection | : yes |
| Detection of faulty battery | : - |
| Protective class | : IP65 |
| Admiss. ambient temp. | : 0-40 °C |
| Dimensions | : 194 x 68 x 47 mm |
| Weight | : 529 g |
| Position | : - |
| Other features | : - |