
-

Tekniske data

| | |
|--------------------------------|---------------------------------|
| Active/passive | : passive |
| Transmission method | : 100 V |
| Total output power | : - |
| Power rating (RMS) | : - |
| Total power rating | : - |
| Power rating (RMS) | : 50/25/12.5 W |
| Impedance | : 4 Ohm |
| Frequency range | : 60-18,000 Hz |
| THD | : - |
| S/N ratio | : - |
| Input signal | : - |
| System | : wideband bass-reflex |
| Full range speaker | : 13 cm (5") full range speaker |
| Bass speaker | : - |
| Midrange speaker | : - |
| Tweeter | : - |
| Number of speakers | : 1 |
| Speaker size | : 13 cm (5") |
| Sensitivity | : 87 dB/W/m |
| Max. rated SPL | : 104 dB |
| Radiation angle, horizontal | : - |
| Radiation angle, vertical | : - |
| Features | : - |
| Housing material | : ABS |
| Colour | : white |
| Mounting device | : mounting bracket |
| Protected against ball rebound | : yes |
| Protection class | : IP45 |
| Admiss. ambient temp. | : -10 °C to +40 °C |
| Power supply | : - |
| Dimensions | : 200 x 200 x 190 mm |
| Width | : 200 mm |
| Height | : 200 mm |
| Depth | : 190 mm |
| Weight | : 5.1 kg |

| | |
|------------------------|------------------|
| Inputs | : screw terminal |
| Outputs | : - |
| Replacement voice coil | : - |
| Other features | : - |
| Accessories | : - |