


HSE-340/SK - Headworn Microphone

new



Professional headband microphone, with cardioid polar pattern and a high-quality sound which is suitable for any vocal or speech application. Innovative design features ensure a maximum suppression of both the impact sound and structure-borne noise as well as an extra low acoustic feedback, very comfortable to wear. Beige version.

- Corrosion-resistant neckband, easy to clean
- Drip ring (protects cartridge from moisture)
- Unobtrusive and secure fit due to cable routing in neck area incl. strain relief and cable bending protection
- Stable positioning
- Microphone windshield
- 4-pole mini XLR inline jack for connection to pocket transmitters from JTS or a pocket transmitters of the same design from other brand manufacturers

Tekniske data

Description	: headband microphone
Version	: -
Transmission method	: cable
Polar pattern	: cardioid
System	: electret
Carrier frequency range	: -
Transmitting power	: -
Power supply	: -
Operating time	: -
Audio frequency range	: 50-18,000 Hz
Nominal impedance	: 2 kOhm
Sensitivity	: 2.3 mV/Pa
S/N ratio	: -
Max. sound pressure	: 120 dB
Power supply	: 1.5-9 V
Gooseneck length	: -
Housing material	: -
Admiss. ambient temp.	: 0-40 °C
Dimensions	: -
Weight	: 18 g (w/o cable and plug)
Cable	: -
Connection	: 4-pole mini XLR