

TXS-2402SET - Wireless Microphone



With the TXS-2402SET, the entry into the world of digital wireless transmission will become a special sound experience. The signal transmission in the 2.4 GHz range is particularly stable and impresses by a high resistance to interference. The system manages without a compander which results in an incredibly dynamic efficiency and a voice transmission with a unique sound quality. Two systems can be used in parallel operation, thus 4 microphone transmission paths can be used simultaneously. Licence-free system. The particularly easy and convenient use of the units and appealing design make the TXS-2402SET a real digital experience for the user. Digital wireless 2-channel PLL microphone system, 2.4 GHz

- 2 microphone transmitters, 1 receiver, 1 plug-in PSU
- High resistance to interference due to digital transmission
- 2 systems can be used in parallel (corresponds to 4 microphone transmission paths)
- 16 frequencies (2,404-2,476 MHz) for each channel can be selected at the transmitter
- Wireless auto-configuration of the receiver
- Volume control for each channel
- 6.3 mm output for mixed signal
- Microphone cartridges of supercardioid characteristic

Licence-free in the EU.

tastenwelt 06/2012

“An entry-level wireless system with a perfectly functioning technology.”

+ Easy operation

+ Well-balanced hand-held transmitter

Tekniske data

General information

| | |
|-------------------------|------------------------------|
| | : - |
| Description | : wireless microphone system |
| Carrier frequency range | : 2,404-2,476 MHz |
| Audio frequency range | : 80-12,000 Hz |
| Channels | : 2 |
| THD | : < 0.1% |
| Dynamic range | : 87 dB |
| RF S/N ratio | : - |
| Operating time | : - |
| Admiss. ambient temp. | : 0-40 °C |
| Power supply | : - |
| Dimensions | : - |
| Total weight | : - |
| Connections | : - |

Specifications transmitter

| | |
|--------------------|--|
| | : - |
| Transmitting power | : 10 mW |
| Operating range | : approx. 30 m (free field) approx. 20 m (indoors) |

| | |
|--------------------------|---------------------------|
| Power supply transmitter | : 2 x 1.5 V batt. AA size |
| Width transmitter | : 54 mm |
| Height transmitter | : 54 mm |
| Depth transmitter | : 225 mm |
| Weight transmitter | : 120 g |
| Connections transmitter | : - |

Specifications receiver

| | |
|-----------------------|----------------------------------|
| | : - |
| Audio signal receiver | : 100 mV/600 Ohm |
| Power supply receiver | : via encl. plug-in power supply |
| Width receiver | : 220 mm |
| Height receiver | : 45 mm |
| Depth receiver | : 150 mm |
| Weight receiver | : 550 g |
| Connections receiver | : 1 x 6.3 mm jack, unbal. |