

---

-

## Tekniske data

### General information

|                         |                      |
|-------------------------|----------------------|
|                         | : -                  |
| Description             | : pocket transmitter |
| Carrier frequency range | : 1,785-1,800 MHz    |
| Audio frequency range   | : 60-16,000 Hz       |
| Channels                | : 1                  |
| THD                     | : -                  |
| Dynamic range           | : -                  |
| RF S/N ratio            | : -                  |
| Operating time          | : ? 8 h              |
| Admiss. ambient temp.   | : 0-40 °C            |
| Power supply            | : -                  |
| Dimensions              | : -                  |
| Total weight            | : -                  |
| Connections             | : -                  |

### Specifications transmitter

|                          |                           |
|--------------------------|---------------------------|
|                          | : -                       |
| Transmitting power       | : 10 mW                   |
| Operating range          | : -                       |
| Power supply transmitter | : 2 x 1.5 V batt. AA size |
| Width transmitter        | : 64 mm                   |
| Height transmitter       | : 102 mm                  |
| Depth transmitter        | : 28 mm                   |
| Weight transmitter       | : 118 g                   |
| Connections transmitter  | : 1 x 3-pole mini XLR     |
| Specifications receiver  | : -                       |
| Audio signal receiver    | : -                       |
| Power supply receiver    | : -                       |
| Width receiver           | : -                       |
| Height receiver          | : -                       |
| Depth receiver           | : -                       |
| Weight receiver          | : -                       |
| Connections receiver     | : -                       |