

## ECM-310W - Electret Microphone



Electret microphone for sound pickup of wind instruments

- 8 cm gooseneck
- Phantom power via supplied adapter
- With 3 m connection cable and clamp
- Supplied in a practical plastic case

## Tekniske data

|                         |   |
|-------------------------|---|
| Description             | : instrument microphone                     |
| Version                 | : -   |
| Transmission method     | : cable                                     |
| Polar pattern           | : supercardioid                             |
| System                  | : electret                                  |
| Carrier frequency range | : -   |
| Transmitting power      | : -   |
| Power supply            | : -   |
| Operating time          | : -   |
| Audio frequency range   | : 30-17,000 Hz                              |
| Nominal impedance       | : 200 Ohm                                   |
| Sensitivity             | : 4.5 mV/Pa                                 |
| S/N ratio               | : -   |
| Max. sound pressure     | : 120 dB                                    |
| Power supply            | : 9-48 V via power supply adapter           |
| Gooseneck length        | : -   |
| Housing material        | : -   |
| Admiss. ambient temp.   | : 0-40 °C                                   |
| Dimensions              | : 140 mm                                    |
| Weight                  | : 155 g                                     |
| Cable                   | : 3 m                                       |
| Connection              | : 3-pole mini XLR, unbal.adapter: XLR, bal. |