

HSE-152A/SK - Headworn Microphone



A series of headband microphones and earband microphones for universal applications, beige version for adapter systems.

With the supplied adapters, suitable for pocket transmitters from MONACOR and JTS. Further connection adapters for devices from other manufacturers are available at option.

Ultra-light headband microphone,
cardioid polar pattern.

This microphone with a back electret cartridge with cardioid polar pattern is suitable for any application requiring a directional sound pick-up. A solid tool with a great sound for presenters and vocalists, even suitable for severe acoustic conditions thanks to the low acoustic feedback. The lightweight and almost invisible headband is very comfortable to wear and keeps the cartridge securely in place.

Connected to a cable with latching device and by using optional adapters, the HSE-152A/SK can be operated with wireless transmission systems of various manufacturers.

- Wide transmission range
- Very comfortable to wear
- Stable positioning
- Turning cartridge arm of adjustable length
- Drip ring (protects cartridge from moisture)
- Removable sweat-proof connection cable with 2.5 mm stereo plug (replacement connection cable: HSE-70C)
- With supplied adapters, compatible with all TXS-...HSE pocket transmitters (3-pole mini XLR) and pocket transmitters from JTS (4-pole mini XLR)
- Optional adapters allow application with devices from other manufacturers
- External power supply e.g. via phantom power supply adapter EMA-1 or EMA-300P
- Windshield

Tekniske data

Description	: headband microphone
Version	: -
Transmission method	: cable
Polar pattern	: cardioid
System	: back electret
Carrier frequency range	: -
Transmitting power	: -
Power supply	: -
Operating time	: -
Audio frequency range	: 20-20,000 Hz
Nominal impedance	: 1.5 kOhm
Sensitivity	: 1.8 mV/Pa
S/N ratio	: -
Max. sound pressure	: 130 dB
Power supply	: DC 1.5-9 V
Gooseneck length	: -
Housing material	: -
Admiss. ambient temp.	: 0-40 °C
Dimensions	: -
Weight	: 7 g
Cable	: -
Connection	: 2.5 mm stereo plug2 connecting adapters