


SP-3RDP - Mini Loudspeaker




Miniature flush-mount speaker, 8 Ohm

- For general applications in models, intercom systems, miniature radios

Miniature flush-mount speaker

Legend scale drawing:

- Width = Ø A
- Depth = E
- Magnet diameter = Ø B
- Mounting cutout = Ø C
- Mounting depth = E-D



Tekniske data

Impedance (Z)	: 8 Ohm
Transmission method	: -
Frequency range	: 350-15,000 Hz
Resonant frequency (fs)	: -
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	: -
Power rating (RMS)	: 0.5 W
Peak music power output (MAX)	: -
Sensitivity	: -
Max. rated SPL	: -
Max. voltage	: -
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Suspension compl. (Cms)	: -
Moving mass (Mms)	: -
Mech. Q factor (Qms)	: -
Electr. Q factor (Qes)	: -
Total Q factor (Qts)	: -
Equivalent volume (Vas)	: -
DC resistance (Re)	: -
Force factor (BxL)	: -
Voice coil induct. (Le)	: -
Voice coil diameter	: -
Voice coil former	: -
Linear excursion (X _{MAX})	: -
Eff. cone area (Sd)	: -
Magnet weight	: -
Magnet diameter	: $\tilde{\text{A}} \sim 22 \text{ mm}$
Mounting cutout	: $\tilde{\text{A}} \sim 71 \text{ mm}$
Mounting depth	: 23 mm
Mounting hole diameter	: -
Hole spacing X-axis	: -
Hole spacing Y-axis	: -
Dimensions	: $\tilde{\text{A}} \sim 77 \text{ mm} \times 23 \text{ mm}$
Outside diameter	: $\tilde{\text{A}} \sim 77 \text{ mm}$
Width	: 77 mm



Height	: -
Depth	: 23 mm
Protective class	: -
Admiss. ambient temp.	: 0-40 °C
Weight	: 0.05 kg
Packing unit	: 1
Type of speaker	: -