


PA-704 - PA Amplifier

100V 4Ω 8Ω 16Ω new



Mono PA mixing amplifier

- 1 x 35 W
- Silent operation due to fanless cooling concept
- 2 low-impedance microphone inputs
- 1 aux input, 1 phono input
- Speaker outputs via screw terminals
- Input and output level controls
- 2-way tone control for the output
- Connection for a microphone talk button to switch off the other sources during announcements
- Mains operation and 12-24 V emergency power operation

Tekniske data

| | |
|-------------------------|--|
| Peak output power | : 70 W |
| Power rating | : 35 W |
| Power rating at 2 Ohm | : - |
| Power rating at 4 Ohm | : - |
| Power rating at 8 Ohm | : - |
| Power rating at 16 Ohm | : - |
| Power rating at 100 V | : - |
| Power rating with 4 Ohm | : - |
| bridged operation | |
| Power rating with 8 Ohm | : - |
| bridged operation | |
| Output impedance | : - |
| Channels | : 4 |
| Zones | : - |
| Inputs | : 5 mV (mic), 210 mV (aux), 5 mV (phono) |

| | |
|-----------------------|----------------------|
| Attenuation factor | : - |
| Frequency range | : 100-18,000 Hz |
| Crossover network | : - |
| Crossover frequency | : - |
| Integrated limiter | : - |
| Equalizer bass | : ± 10 dB/150 Hz |
| Equalizer midrange | : - |
| Equalizer treble | : ± 10 dB/6 kHz |
| S/N ratio | : ? 55 dB |
| Crosstalk attenuation | : - |
| THD | : < 1% |

| | |
|--|-------------------|
| Phantom power | : - |
| Mains voltage | : \approx 230 V |
| Mains frequency | : 50 Hz |
| Power consumption, operation | : 100 VA |
| Power consumption, standby | : - |
| Standby current | : - |
| Operating voltage (possible alternative) | : DC 12-24 V |
| Power supply (possible alternative) | : DC 2.5 A |
| Admiss. ambient temp. | : 0-40 °C |

Width
Height

: 320 mm
: 85 mm





| | |
|-----------------|--|
| Depth | : 230 mm |
| Rack spaces, RS | : - |
| Weight | : 4.97 kg |
| Connections | : 2 x 6.3 mm jack (mic), 1 x RCA L/R (aux), 1 x RCA L/R (phono), connecting terminals (speakers) |