

## MPX-44/SW - Stereo Mixer



6-channel stereo DJ mixer,  
with black brushed aluminium front panel.

- 6 input channels (4 stereo ways, 2 microphone ways)
- Stereo input channels, switchable 2 x phono/line and 2 x line/line, with LED level display of the stereo master
- Input channels, each with gain control and 3-way equalizer, stereo input channels with cut function
- DJ mic with automatic talkover, PAD switch and on-air switch
- Mic with PAD switch and on-air switch
- Switches illuminate blue when activated
- Adjustable, crossfader-controlled headphone output with pre-fader listening (PFL) to the stereo input channels and mic
- Replaceable crossfader with assignment switches
- Especially easy-sliding high-quality faders
- Master output with stereo LED level display
- Additional outputs booth and zone
- Connection for gooseneck light GNL-204

## Tekniske data

No. of channels	: 6
No. of inputs	: 12
Mic input	: 1.5 mV, 2 x 6.3 mm jack
Line input	: 150 mV, 5 x RCA L/R
CD input	: 150 mV, 1 x RCA L/R
Phono input	: 3 mV, 2 x RCA L/R
Tape (play)	: -
Aux input	: -
Insert input	: -
Effect return	: -
Master output	: 1 V/600 Ohm, 1 x 3-pole XLR, 1 x RCA L/R
Record output	: 0.5 V/600 Ohm, 1 x RCA L/R
Monitor output	: 1 V/600 Ohm (zone), 1 x RCA L/R
Booth output	: 1 V/600 Ohm, 1 x RCA L/R
Aux output	: -
Insert output	: -
Effect send	: -
Control room	: -
Tape (rec)	: -
Headphones	: 8 Ohm, 1 x 6.3 mm jack
Gooseneck lamp	: 12 V/0.75 W, 1 x BNC
WiFi	: -
USB	: -
<b>Bluetooth</b>	: -
Frequency range	: 20-20,000 Hz
THD	: 0.1%
S/N ratio	: 61 dB, unweighted
Crosstalk	: -
Equalizer bass	: +12 dB, -12 dB/50 Hz (mic) +15 dB, -30 dB/50 Hz (channels 1-4)
Equalizer midrange	: +12 dB, -12 dB/1 kHz (mic) +15 dB, -30 dB/1 kHz (channels 1-4)
Equalizer treble	: +12 dB, -12 dB/10 kHz (mic) +15 dB, -30 dB/10 kHz (channels 1-4)
equalizer	: -
Talkover	: -16 dB, automatic
Phantom power	: -
Crossfader	: yes

Media player	: -
Amplifier	: -
Power supply	: &acd;230Â V/50Â Hz/20Â VA
Mains voltage	: &sim; 230 V
Mains frequency	: 50 Hz
Power consumption, operation	: 20 VA
Operating voltage (possible alternative)	: -
Power supply (possible alternative)	: -
Admiss. ambient temp.	: 0-40 °C
Width	: 482 mm
Height	: 177 mm
Depth	: 105 mm
Rack spaces, RS	: 4
Weight	: 3.6 kg