

# HSE-70WP - Headworn Microphone

IPX4



Splashproof electret headband microphone, IPX4

- Suitable for vocal and speech applications, especially with outdoor activities or with high ambient humidity
- Very comfortable to wear
- Secure fit also for sports applications
- Back electret microphone cartridge with cardioid polar pattern
- 3-pole mini XLR inline jack for connection to an optional phantom power supply adapter (EMA-1, EMA-300P) or a pocket transmitter TXS-...HSE
- Supplied with nylon bag

## Tekniske data

|                         |                       |
|-------------------------|-----------------------|
| Description             | : headband microphone |
| Version                 | : -                   |
| Transmission method     | : cable               |
| Polar pattern           | : cardioid            |
| System                  | : back electret       |
| Carrier frequency range | : -                   |
| Transmitting power      | : -                   |
| Power supply            | : -                   |
| Operating time          | : -                   |
| Audio frequency range   | : 100-14,000 Hz       |
| Nominal impedance       | : 600 Ohm             |
| Sensitivity             | : 7.9 mV/Pa           |
| S/N ratio               | : -                   |
| Max. sound pressure     | : 115 dB              |
| Power supply            | : DC 1.5-9 V          |
| Gooseneck length        | : -                   |
| Housing material        | : -                   |
| Admiss. ambient temp.   | : 0-40 °C             |
| Dimensions              | : -                   |
| Weight                  | : 60 g                |
| Cable                   | : 1.1 m               |
| Connection              | : 3-pole mini XLR     |