

DRM-884RC - Paging Microphone



PA zone paging microphone,
for audio matrix router DRM-884.

- LCD for selected zones (1-32), volume and ID number
- LED indication for signal status
- Volume control (assignable for each zone)
- Zone selector control
- Momentary push-to-talk button
- Plug-in electret gooseneck microphone (NEUTRIK 3-pole XLR jack)
- USB port for loading sound files containing chimes
- Power supply via audio matrix router DRM-884
- Connection to DRM-884 via RJ45 jack and Cat. 5e network cable (supplied w/o cable), cable length up to 100 m

Tekniske data

| | |
|-------------------------|-----------------------------|
| Description | : PA zone paging microphone |
| Version | : - |
| Transmission method | : cable |
| Polar pattern | : - |
| System | : - |
| Carrier frequency range | : - |
| Transmitting power | : - |
| Power supply | : - |
| Operating time | : - |
| Audio frequency range | : - |
| Nominal impedance | : - |
| Sensitivity | : - |
| S/N ratio | : - |
| Max. sound pressure | : - |
| Power supply | : - |
| Gooseneck length | : 310 mm |
| Housing material | : - |
| Admiss. ambient temp. | : 0-40 °C |
| Dimensions | : 176 x 70 x 162 mm |
| Weight | : 811 g |
| Cable | : - |
| Connection | : RJ45, micro USB |