

## FGA-40 - Ground Insulator



### **Ground isolator,**

for preventing signal interference and hum loops which may occur, e.g. when connecting the car radio to an amplifier.

- Galvanically isolated inputs and outputs
- RCA plugs and RCA jacks
- Input/output impedance: 15 kOhm
- Frequency range: 20-30,000 Hz
- THD: < 0.001%
- Transmission ratio 1:1
- Ø 35 mm x 65 mm, 65 g

## Tekniske data

Description	: ground isolator
Frequency range	: 20-30,000 Hz
Control range	: -
Control frequencies	: -
Input signal	: -
Input sensitivity	: -
Input impedance	: 15 kOhm
Output signal	: -
Output impedance	: 15 kOhm
Gain	: -
Phantom power	: -
Compression	: -
Gate ratio	: -
Crossover frequency	: -
High-pass filter	: -
Low cut	: -
Transmission ratio	: 1:1
S/N ratio	: -
Channel separation	: -
THD	: < 0.001%
Admiss. ambient temp.	: 0-40 °C
Power supply	: -
Dimensions	: ~ 35 mm x 65 mm
Weight	: 98 g
Inputs	: 1 x RCA plug L/R
Outputs	: 1 x RCA inline jack L/R
Other features	: -