

## FGA-35 - Ground Insulator



### **Ground isolator,**

compact design, for preventing signal interference and hum loops which may occur, e.g. when connecting PC sound cards or laptops to an amplifier.

- Galvanically isolated inputs and outputs
- 2 x 3.5 mm stereo plug
- Input/output impedance: 20 kOhm
- Frequency range: 20-30,000 Hz
- THD: < 0.01%
- Transmission ratio 1:1
- Ø 24 mm x 38 mm, 32 g
- Length including connection cable: approx. 80 cm

### **TASTENWELT 04/2014**

“The FGA-35 is a compact transmitter and ideally suited for connecting instruments (e.g. stage pianos) to an audio device without interference.”

## Tekniske data

Description	: ground isolator
Frequency range	: 20-30,000 Hz
Control range	: -
Control frequencies	: -
Input signal	: -
Input sensitivity	: -
Input impedance	: 20 kOhm
Output signal	: -
Output impedance	: 20 kOhm
Gain	: -
Phantom power	: -
Compression	: -
Gate ratio	: -
Crossover frequency	: -
High-pass filter	: -
Low cut	: -
Transmission ratio	: 1:1
S/N ratio	: -
Channel separation	: -
THD	: < 0.01%
Admiss. ambient temp.	: 0-40 °C
Power supply	: -
Dimensions	: 24 mm x 38 mm
Weight	: 31 g
Inputs	: 1 x 3.5 mm stereo plug
Outputs	: 1 x 3.5 mm stereo plug
Other features	: -