

ECMS-90 - Studio Condenser Microphone



Large diaphragm condenser microphone,
for professional studio applications.

- 2.8 cm (1.1") extra thin gold-plated diaphragm
- Low cut switch
- 10 dB attenuation, switchable
- 48 V phantom power
- Supplied with vibration absorbing support (spider) with 16 mm ((tm)) tripod socket and 9 mm ((tm)) adapter screw, microphone windshield and leather bag
- Supplied in a foam-padded case

tools4music 01/2018

"Great quality at an attractive price"

delamar.de 04/2018

"Affordable large diaphragm condenser microphone with cardioid polar pattern, filter, pad and spider: the ECMS-90 from IMG STAGELINE impresses with an absolutely perfect performance in its price class. I really like the well-balanced sound ... It provides a percussive sound which is rich in detail and hardly changes, even if the perfect angle for positioning the microphone deviates by more than 30°. The background noise is almost non-existent. It also features high-quality accessories and impeccable workmanship. All in all, a top microphone for ambitious home recording."

Tekniske data

| | |
|-------------------------|------------------------------|
| Description | : large diaphragm microphone |
| Version | : - |
| Transmission method | : cable |
| Polar pattern | : cardioid |
| System | : condenser |
| Carrier frequency range | : - |
| Transmitting power | : - |
| Power supply | : - |
| Operating time | : - |
| Audio frequency range | : 20-20,000 Hz |
| Nominal impedance | : 200 Ohm |
| Sensitivity | : 20 mV/Pa |
| S/N ratio | : 78 dB |
| Max. sound pressure | : 135 dB |
| Power supply | : DC 48 V, phantom power |
| Gooseneck length | : - |
| Housing material | : metal |
| Admiss. ambient temp. | : 0-40 °C |
| Dimensions | : Å~ 50 mm x 185 mm |
| Weight | : 430 g |
| Cable | : - |
| Connection | : XLR, bal. |