

ESP-80/WS - PA Wall Speaker



PA wall speaker,
vandal-resistant.

- 100 V line technique via audio transformer with 4 power taps
- Full range speaker with a good voice reproduction, suitable for background music
- Very robust 2-piece metal housing

Tekniske data

| | |
|--------------------------------|---------------------|
| Active/passive | : passive |
| Transmission method | : 100 V |
| Total output power | : - |
| Power rating (RMS) | : - |
| Total power rating | : - |
| Power rating (RMS) | : 6/3/1.5/0.75 W |
| Impedance | : - |
| Frequency range | : 250-10,000 Hz |
| THD | : - |
| S/N ratio | : - |
| Input signal | : - |
| System | : - |
| Full range speaker | : - |
| Bass speaker | : - |
| Midrange speaker | : - |
| Tweeter | : - |
| Number of speakers | : - |
| Speaker size | : - |
| Sensitivity | : - |
| Max. rated SPL | : - |
| Radiation angle, horizontal | : - |
| Radiation angle, vertical | : - |
| Features | : - |
| Housing material | : metal |
| Colour | : white |
| Mounting device | : - |
| Protected against ball rebound | : - |
| Protection class | : - |
| Admiss. ambient temp. | : 0-40 °C |
| Power supply | : - |
| Dimensions | : 170 x 170 x 63 mm |
| Width | : 170 mm |
| Height | : 170 mm |
| Depth | : 63 mm |
| Weight | : 1.5 kg |



| | |
|------------------------|-----|
| Inputs | : - |
| Outputs | : - |
| Replacement voice coil | : - |
| Other features | : - |
| Accessories | : - |