

## ILA-100XLR - Attenuator



Passive stereo level control (XLR version),  
for a precise volume control of line signals,  
for inserting between analogue signal sources and amplifiers or active speakers, e.g. between a PC sound  
card and active speaker systems.

- 2 x balanced comb. input (XLR/6.3 mm jack), 1 x 3.5 mm stereo input
- 2 x balanced XLR output, 1 x 3.5 mm stereo output
- Large, easy-turning level control
- Mute button
- Frequency range: 20-20,000 Hz
- Passive, no power supply required
- High-quality metal console housing with brushed aluminium front panel
- Dimensions: 142 x 60 x 86 mm
- Weight: 300 g

## Tekniske data

Impedance	: -
Line input	: -
Input control voltage	: -
Line output	: -
Output control voltage	: -
Channels	: 2
Attenuation	: -
Attenuation direction	: -
Turning angle	: -
Frequency range	: 20-20,000 Hz
THD	: -
S/N ratio	: -
Power rating	: -
Power supply	: -
Admiss. ambient temp.	: 0-40 °C
Dimensions	: 142 x 60 x 86 mm
Weight	: 300 g
Connections	: 2 x comb. balanced input (XLR/6.3 mm jack), 1 x 3.5 mm stereo input, 2 x balanced XLR output, 1 x 3.5 mm stereo output