

EUL-26/WS - PA Speaker Cabinets



Pairs of miniature PA speaker systems

- Speakers for general applications, very small dimensions in 100 V technology
- Can also be connected at 8 Ohm
- 6.5 cm (2.5") full range speaker
- Good sound characteristics and speech intelligibility
- Turnable, movable and tiltable due to wall bracket with ball joint
- For completing the low-frequency sound reproduction, an additional subwoofer system is recommended (e.g. EUL-2SUB/SW, SOUND-100SUB)

Tekniske data

Active/passive	: passive
Transmission method	: 100 V
Total output power	: -
Power rating (RMS)	: -
Total power rating	: 20 W
Power rating (RMS)	: 6 W (100 V) 10 W (8 Ohm)
Impedance	: 8 Ohm
Frequency range	: 150-20,000 Hz
THD	: -
S/N ratio	: -
Input signal	: -
System	: -
Full range speaker	: -
Bass speaker	: -
Midrange speaker	: -
Tweeter	: -
Number of speakers	: 1
Speaker size	: 6.5 cm (2.5")
Sensitivity	: 88 dB/W/m
Max. rated SPL	: -
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Features	: -
Housing material	: -
Colour	: white
Mounting device	: wall bracket
Protected against ball rebound	: -
Protection class	: -
Admiss. ambient temp.	: 0-40 °C
Power supply	: -
Dimensions	: 90 x 90 x 115 mm
Width	: 90 mm
Height	: 90 mm
Depth	: 115 mm
Weight	: 0.65 kg



Inputs	: spring-load. speaker term.
Outputs	: -
Replacement voice coil	: -
Other features	: pair
Accessories	: -