

## WALL-04T/SW - PA Speaker Cabinet



Pair of 2-way PA speaker systems

- 100 V wall speaker with plastic cabinet in black
- 4 power taps as well as switchable to 8 Ohm operation
- 10 cm (4") bass-midrange speaker and 12 mm (½") dome tweeter
- Suitable for outdoor applications (IP65)
- Weatherproof
- High sound quality and speech intelligibility
- Mounting bracket for pivoting and tilting
- Connecting terminal with cover

## Tekniske data

|                                |                                      |
|--------------------------------|--------------------------------------|
| Active/passive                 | : passive                            |
| Transmission method            | : 100 V                              |
| Total output power             | : -                                  |
| Power rating (RMS)             | : -                                  |
| Total power rating             | : 60 W                               |
| Power rating (RMS)             | : 16/8/4/2 W (100 V)<br>30 W (8 Ohm) |
| Impedance                      | : 8 Ohm                              |
| Frequency range                | : 90-20,000 Hz                       |
| THD                            | : -                                  |
| S/N ratio                      | : -                                  |
| Input signal                   | : -                                  |
| System                         | : 2-way                              |
| Full range speaker             | : -                                  |
| Bass speaker                   | : 10 cm (4") bass-midrange speaker   |
| Midrange speaker               | : -                                  |
| Tweeter                        | : 12 mm (½") dome tweeter            |
| Number of speakers             | : 2                                  |
| Speaker size                   | : 4"                                 |
| Sensitivity                    | : 87 dB/W/m                          |
| Max. rated SPL                 | : 100 dB                             |
| Radiation angle, horizontal    | : -                                  |
| Radiation angle, vertical      | : -                                  |
| Features                       | : -                                  |
| Housing material               | : plastic                            |
| Colour                         | : black                              |
| Mounting device                | : mounting bracket                   |
| Protected against ball rebound | : -                                  |
| Protection class               | : IP65                               |
| Admiss. ambient temp.          | : 0-40 °C                            |
| Power supply                   | : -                                  |
| Dimensions                     | : 130 x 197 x 164 mm (with bracket)  |
| Width                          | : 130 mm                             |
| Height                         | : 197 mm                             |
| Depth                          | : 164 mm                             |
| Weight                         | : 1.8 kg                             |



|                        |                              |
|------------------------|------------------------------|
| Inputs                 | : spring-load. speaker term. |
| Outputs                | : -                          |
| Replacement voice coil | : -                          |
| Other features         | : for pivoting and tilting   |
| Accessories            | : -                          |