

PAB-52WP/WS - PA Speaker Cabinet



Weatherproof PA speakers with IP classification.

Exactly the right speakers whenever a high sound quality, a high volume capability and a respective resistance to all weather conditions are required. Ideally suited for permanent open-air applications, e.g. at fairground attractions, PA applications in pedestrian areas, at sports facilities and wherever a weather-protected installation of the speakers is not possible.

Weatherproof high-performance PA speaker system, 50 W

- Compact wideband bass-reflex system in an ABS cabinet
- 100 V or 4 Ohm operation, selectable
- 13 cm (5") high-quality full range speaker with aluminium cone
- Excellent sound characteristics
- Front grille with water-repellent gauze
- Recessed connection terminal with cover plate and high-strength cable gland
- Metal parts and wall bracket made of stainless steel
- Ball-proof according to DIN 18032, Part 3

PROSOUND 05/2011

"The cabinets give a solid impression ... and meet IP45 requirements. All four speaker systems are suitable for pleasant background music ... the large PAB-8WP/WS is capable of quite high volume levels ... however, the small ones should not be underestimated ... these speaker systems are impressive and the price is quite reasonable for weatherproof speaker systems."

Tekniske data

Active/passive	: passive
Transmission method	: 100 V
Total output power	: -
Power rating (RMS)	: -
Total power rating	: -
Power rating (RMS)	: 50/25/12.5 W
Impedance	: 4 Ohm
Frequency range	: 60-18,000 Hz
THD	: -
S/N ratio	: -
Input signal	: -
System	: wideband bass-reflex
Full range speaker	: 13 cm (5") full range speaker
Bass speaker	: -
Midrange speaker	: -
Tweeter	: -
Number of speakers	: 1
Speaker size	: 13 cm (5")
Sensitivity	: 87 dB/W/m
Max. rated SPL	: 104 dB
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Features	: -
Housing material	: ABS
Colour	: white
Mounting device	: mounting bracket
Protected against ball rebound	: yes
Protection class	: IP45
Admiss. ambient temp.	: -10 °C to +40 °C
Power supply	: -
Dimensions	: 200 x 200 x 190 mm
Width	: 200 mm
Height	: 200 mm
Depth	: 190 mm
Weight	: 5.1 kg



Inputs	: screw terminal
Outputs	: -
Replacement voice coil	: -
Other features	: -
Accessories	: -