


EDL-70/WS - PA Loudspeaker

100V



PA ceiling speaker,
with special 2-step mounting.

- 100 V line technique
- Snap-in mounting
- For a ceiling thickness from 2 to 45 mm
- Full range speaker with a clear voice reproduction
- Wide frequency range
- Robust metal version (basket and protective grille)

For mounting this PA ceiling speaker, the mounting frame is attached to the ceiling cutout at first via the snap-in system. Then, the speaker is inserted into the frame with a bayonet-type locking. A safety rope provides additional safety.

Tekniske data

Impedance (Z)	: -
Transmission method	: 100 V
Frequency range	: 90-20,000 Hz
Resonant frequency (fs)	: -
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	: -
Power rating (RMS)	: 6/3/1.5 W
Peak music power output (MAX)	: -
Sensitivity	: 97 dB/W/m
Max. rated SPL	: -
Max. voltage	: -
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Suspension compl. (Cms)	: -
Moving mass (Mms)	: -
Mech. Q factor (Qms)	: -
Electr. Q factor (Qes)	: -
Total Q factor (Qts)	: -
Equivalent volume (Vas)	: -
DC resistance (Re)	: -
Force factor (BxL)	: -
Voice coil induct. (Le)	: -
Voice coil diameter	: -
Voice coil former	: -
Linear excursion (X _{MAX})	: -
Eff. cone area (Sd)	: -
Magnet weight	: -
Magnet diameter	: -
Mounting cutout	: \varnothing 195 mm
Mounting depth	: 100 mm
Mounting hole diameter	: -
Hole spacing X-axis	: -
Hole spacing Y-axis	: -
Dimensions	: \varnothing 220 mm x 104 mm
Outside diameter	: \varnothing 220 mm
Width	: \varnothing 220 mm



Height	: -
Depth	: 104 mm
Protective class	: -
Admiss. ambient temp.	: 0-40 °C
Weight	: 1 kg
Packing unit	: -
Type of speaker	: 165