




ESP-17/WS - PA Wall Speaker

100V



ESP-17/WS



PA hi-fi wall and ceiling speakers

- 100 V line technique, 2-way version with dome tweeter (movable with ESP-17/WS, ESP-22/WS and ESP-32/WS)
- Plastic housing with protective metal grille
- ABS plastic material, self-extinguishing according to UL 94V-0
- Excellent sound characteristics
- For a wall thickness/ceiling thickness from 8 to 35 mm

Tekniske data

Impedance (Z)	: -
Transmission method	: 100 V
Frequency range	: 55-20,000 Hz
Resonant frequency (fs)	: -
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	: -
Power rating (RMS)	: 15/7.5/4/2/1 W
Peak music power output (MAX)	: -
Sensitivity	: 87 dB/W/m
Max. rated SPL	: -
Max. voltage	: -
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Suspension compl. (Cms)	: -
Moving mass (Mms)	: -
Mech. Q factor (Qms)	: -
Electr. Q factor (Qes)	: -
Total Q factor (Qts)	: -
Equivalent volume (Vas)	: -
DC resistance (Re)	: -
Force factor (BxL)	: -
Voice coil induct. (Le)	: -
Voice coil diameter	: -
Voice coil former	: -
Linear excursion (X _{MAX})	: -
Eff. cone area (Sd)	: -
Magnet weight	: -
Magnet diameter	: -
Mounting cutout	: 270 x 185 mm
Mounting depth	: 80 mm
Mounting hole diameter	: -
Hole spacing X-axis	: -
Hole spacing Y-axis	: -
Dimensions	: 300 x 214 x 90 mm
Outside diameter	: -
Width	: 300 mm



Height	: 214 mm
Depth	: 90 mm
Protective class	: -
Admiss. ambient temp.	: 0-40 °C
Weight	: 1.9 kg
Packing unit	: -
Type of speaker	: 130