-

Tekniske data

Active/passive	:	active
Transmission method	:	wireless/cable
Total output power	:	200 W
Power rating (RMS)	:	120 W
Total power rating	:	-
Power rating (RMS)	:	-
Impedance	:	-
Frequency range	:	45-20,000 Hz
THD	:	-
S/N ratio	:	-
Input signal	:	600 mV/8 kOhm (line, XLR, bal.),500 mV/8 kOhm (line, RCA/3.5 mm jack),30 mV/1 kOhm (mic, XLR, bal.),75 mV/2 kOhm (mic, 6.3 mm jack)
System	:	15/2 full range bass-reflex
Full range speaker	:	-
Bass speaker	:	38 cm (15") bass speaker
Midrange speaker	:	-
Tweeter	:	25 mm (1") horn tweeter
Number of speakers	:	2
Speaker size	:	38 cm (15")
Sensitivity	:	96 dB/W/m
Max. rated SPL	:	117 dB
Radiation angle, horizontal	:	-
Radiation angle, vertical	:	-
Features	:	-
Housing material	:	plastic
Colour	:	black
Mounting device	:	M8 threaded inserts, stand sleeve
Protected against ball rebound	:	-
Protection class	:	-
Admiss. ambient temp.	:	0-40 °C
Power supply	:	∿ 230Â V/50Â Hz/220Â VA
Dimensions	:	445 x 700 x 360Â mm
Width	:	445 mm
Height	:	700 mm
Depth	:	360 mm
Weight	:	13 kg

Inputs	: XLR, RCA L/R or 3.5Â mmÂ jack(line),XLR or 6.3Â mm jack (mic)
Outputs	: XLR, bal. (mix out)
Replacement voice coil	: -
Other features	: castors
Accessories	: -