

## SP-17/4 - Universal Loudspeaker



Universal speaker, 30 W, 4 Ohm

- For general applications and replacement purposes
- High power capability
- To be used in the bass-midrange

## Tekniske data

Impedance (Z)	: 4 Ohm
Transmission method	: -
Frequency range	: f3-6,000 Hz
Resonant frequency (fs)	: -
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	: -
Power rating (RMS)	: 30 W
Peak music power output (MAX)	: 60 W
Sensitivity	: 89 dB/W/m
Max. rated SPL	: -
Max. voltage	: -
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Suspension compl. (Cms)	: mm/N
Moving mass (Mms)	: -
Mech. Q factor (Qms)	: -
Electr. Q factor (Qes)	: -
Total Q factor (Qts)	: -
Equivalent volume (Vas)	: -
DC resistance (Re)	: -
Force factor (BxL)	: -
Voice coil induct. (Le)	: -
Voice coil diameter	: -
Voice coil former	: -
Linear excursion (X <sub>MAX</sub> )	: -
Eff. cone area (Sd)	: -
Magnet weight	: -
Magnet diameter	: Å~ 100 mm
Mounting cutout	: Å~ 147 mm
Mounting depth	: 71 mm
Mounting hole diameter	: Å~ 160 mm
Hole spacing X-axis	: -
Hole spacing Y-axis	: -
Dimensions	: Å~ 169 mm x 79 mm
Outside diameter	: Å~ 169 mm
Width	: Å~ 169 mm



Height	: -
Depth	: 79 mm
Protective class	: -
Admiss. ambient temp.	: 0-40 °C
Weight	: 1.086 kg
Packing unit	: 1
Type of speaker	: 6.5"