



SP-202E - Woofer



Hi-fi bass-midrange speaker, 50 W, 4 Ohm

- All-round speaker
- Foam surround
- Replacement speaker for closed speaker systems

HOBBY HIFI 04/2013

"A very talented 2-way speaker, thanks to a very clean reproduction of the midrange. Despite a very attractive price, the SP-202E from MONACOR is ideally suited for 2-way applications and promises an excellent sound quality."

Tekniske data

Impedance (Z)	: 4 Ohm
Transmission method	: -
Frequency range	: f3-6,000 Hz
Resonant frequency (fs)	: 51 Hz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	: -
Power rating (RMS)	: 50 W
Peak music power output (MAX)	: 100 W
Sensitivity	: 93 dB/W/m
Max. rated SPL	: -
Max. voltage	: -
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Suspension compl. (Cms)	: 0.62 mm/N
Moving mass (Mms)	: 15 g
Mech. Q factor (Qms)	: 4.5
Electr. Q factor (Qes)	: 0.81
Total Q factor (Qts)	: 0.69
Equivalent volume (Vas)	: 39 l
DC resistance (Re)	: 3.85 Ohm
Force factor (BxL)	: 4.86 Tm
Voice coil induct. (Le)	: 0.6 mH
Voice coil diameter	: $\varnothing \sim 25.5$ mm
Voice coil former	: aluminium
Linear excursion (X _{MAX})	: ± 2.5 mm
Eff. cone area (Sd)	: 210 cm ²
Magnet weight	: 570 g
Magnet diameter	: -
Mounting cutout	: $\varnothing \sim 183$ mm
Mounting depth	: 82 mm
Mounting hole diameter	: $\varnothing \sim 192$ mm
Hole spacing X-axis	: -
Hole spacing Y-axis	: -
Dimensions	: $\varnothing \sim 202$ mm x 82 mm
Outside diameter	: $\varnothing \sim 202$ mm
Width	: $\varnothing \sim 202$ mm



Height	: -
Depth	: 82 mm
Protective class	: -
Admiss. ambient temp.	: 0-40 °C
Weight	: 1.39 kg
Packing unit	: 1
Type of speaker	: 8"