

## WAVE-08A - Active PA Speaker



### Pure Entertainment!

The PA speaker systems of the WAVE series impress with a great sound and an attractive price. They are suitable for smaller to medium-sized function rooms and are the perfect starting equipment for entry-level DJs. The plastic cabinets of contemporary design are also lightweight and easy to use. Thus, they are ideally suited for mobile applications.

Active full range speaker system, 150 W

- Compact 8/2 full range bass-reflex system with plastic cabinet
- 20 cm (8") bass speaker and 25 mm (1") horn tweeter
- Integrated MP3 player with USB/SD slot
- Bluetooth receiver
- Infrared remote control
- Balanced mic input via XLR jack or 6.3 mm jack
- Line input via RCA jack or XLR jack
- 2-way tone control for treble and bass
- MIX OUT via XLR jack or 6.3 mm jack
- M8 threaded inserts for mounting support
- Stand sleeve

## Tekniske data

|                                |   |
|--------------------------------|---|
| Active/passive                 | : active  |
| Transmission method            | : wireless/cable  |
| Total output power             | : 150 W   |
| Power rating (RMS)             | : 80 W  |
| Total power rating             | : -   |
| Power rating (RMS)             | : -   |
| Impedance                      | : -   |
| Frequency range                | : 65-20,000 Hz  |
| THD                            | : -   |
| S/N ratio                      | : -   |
| Input signal                   | : 250 mV/7 kOhm (line, XLR, bal.), 150 mV/16 kOhm (line, RCA), 9.5 mV/0.8 kOhm (mic, XLR, bal.), 9.5 mV/0.8 kOhm (mic, 6.3 mm jack) |
| System                         | : 8/2 full range bass-reflex  |
| Full range speaker             | : -   |
| Bass speaker                   | : 20 cm (8") bass speaker   |
| Midrange speaker               | : -   |
| Tweeter                        | : 25 mm (1") horn tweeter   |
| Number of speakers             | : 2   |
| Speaker size                   | : 20 cm (8")  |
| Sensitivity                    | : 95 dB/W/m   |
| Max. rated SPL                 | : 116 dB  |
| Radiation angle, horizontal    | : 90°   |
| Radiation angle, vertical      | : 60°   |
| Features                       | : -   |
| Housing material               | : plastic   |
| Colour                         | : black   |
| Mounting device                | : M8 threaded inserts, stand sleeve   |
| Protected against ball rebound | : -   |
| Protection class               | : -   |
| Admiss. ambient temp.          | : 0-40 °C   |
| Power supply                   | : &acd; 230 V/50 Hz/160 VA  |
| Dimensions                     | : 260 x 420 x 210Å mm   |
| Width                          | : 260 mm  |
| Height                         | : 420 mm  |
| Depth                          | : 210 mm  |
| Weight                         | : 7 kg  |

|                        |  |
|------------------------|--|
| Inputs                 | : XLR or RCA L/R (line) XLR or 6.3 mm jack (mic) |
| Outputs                | : XLR, bal. (parallel line out)                  |
| Replacement voice coil | : -  |
| Other features         | : -  |
| Accessories            | : -  |