

---

-

## Tekniske data

Active/passive	: active
Transmission method	: -
Total output power	: -
Power rating (RMS)	: 2 x 30 W
Total power rating	: -
Power rating (RMS)	: -
Impedance	: -
Frequency range	: 45-20,000 Hz
THD	: -
S/N ratio	: -
Input signal	: Bluetooth 500 mV/10 kOhm
System	: 2-way
Full range speaker	: -
Bass speaker	: 10 cm (4") bass speaker
Midrange speaker	: -
Tweeter	: 25 mm dome tweeter
Number of speakers	: 2
Speaker size	: 10 cm (4")
Sensitivity	: 85 dB/W/m (each speaker system)
Max. rated SPL	: 98 dB (each speaker system)
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Features	: -
Housing material	: MDF
Colour	: white
Mounting device	: -
Protected against ball rebound	: -
Protection class	: -
Admiss. ambient temp.	: 0-40 °C
Power supply	: &acd; 230 V/50 Hz/170 VA
Dimensions	: 140 x 215 x 170Å mm
Width	: 140 mm
Height	: 215 mm
Depth	: 170 mm
Weight	: 5.2Å kg (pair)

Inputs	: 1 x RCA L/R 1 x 3.5 mm stereo jack 1 x Toslink, optical digital input spring-load. speaker term. for passive sp. system
Outputs	: -
Replacement voice coil	: -
Other features	: Bluetooth 4.0, APTX, remote control
Accessories	: -