

## MKA-50SET/SW - Active Cabinets



Active 2-way stereo speaker systems, 2 x 20 W

- Set consists of an active and a passive speaker system. Connection of the passive system to the active system via spring-loaded speaker terminals
- Active speaker system with integrated 2-channel amplifier and power supply
- Speakers with magnetic shielding
- Auto-standby function
- Volume control and 2-way tone control

## Tekniske data

|                                |                                    |
|--------------------------------|------------------------------------|
| Active/passive                 | : active/passive                   |
| Transmission method            | : -                                |
| Total output power             | : 2 x 40 W                         |
| Power rating (RMS)             | : 2 x 20 W                         |
| Total power rating             | : -                                |
| Power rating (RMS)             | : -                                |
| Impedance                      | : -                                |
| Frequency range                | : 60-20,000 Hz                     |
| THD                            | : -                                |
| S/N ratio                      | : -                                |
| Input signal                   | : 420 mV/24 kOhm                   |
| System                         | : 2-way                            |
| Full range speaker             | : -                                |
| Bass speaker                   | : 13 cm (5") bass-midrange speaker |
| Midrange speaker               | : -                                |
| Tweeter                        | : 2.5 cm (1") tweeter              |
| Number of speakers             | : 2                                |
| Speaker size                   | : 13 cm (5")                       |
| Sensitivity                    | : 89 dB/W/m                        |
| Max. rated SPL                 | : 102 dB                           |
| Radiation angle, horizontal    | : -                                |
| Radiation angle, vertical      | : -                                |
| Features                       | : -                                |
| Housing material               | : plastic                          |
| Colour                         | : black                            |
| Mounting device                | : mounting bracket                 |
| Protected against ball rebound | : -                                |
| Protection class               | : -                                |
| Admiss. ambient temp.          | : 0-40 °C                          |
| Power supply                   | : &acd; 230 V/50 Hz/110 VA         |
| Dimensions                     | : 180 x 250 x 160 mm               |
| Width                          | : 180 mm                           |
| Height                         | : 250 mm                           |
| Depth                          | : 160 mm                           |
| Weight                         | : 5.9Â kg (pair)                   |



|                        |                                                                                                  |
|------------------------|--------------------------------------------------------------------------------------------------|
| Inputs                 | : 1 x RCA L/R (active speak. system only) 1 x 3.5 mm jack screw terminals (both speaker systems) |
| Outputs                | : -                                                                                              |
| Replacement voice coil | : -                                                                                              |
| Other features         | : pair                                                                                           |
| Accessories            | : -                                                                                              |