

## MKA-50SET/WS - Active Cabinets



Active 2-way stereo speaker systems, 2 x 20 W

- Set consists of an active and a passive speaker system. Connection of the passive system to the active system via spring-loaded speaker terminals
- Active speaker system with integrated 2-channel amplifier and power supply
- Speakers with magnetic shielding
- Auto-standby function
- Volume control and 2-way tone control

## Tekniske data

Active/passive	: active/passive
Transmission method	: -
Total output power	: 2 x 40 W
Power rating (RMS)	: 2 x 20 W
Total power rating	: -
Power rating (RMS)	: -
Impedance	: -
Frequency range	: 60-20,000 Hz
THD	: -
S/N ratio	: -
Input signal	: 420 mV/24 kOhm
System	: 2-way
Full range speaker	: -
Bass speaker	: 13 cm (5") bass-midrange speaker
Midrange speaker	: -
Tweeter	: 2.5 cm (1") tweeter
Number of speakers	: 2
Speaker size	: 13 cm (5")
Sensitivity	: 89 dB/W/m
Max. rated SPL	: 102 dB
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Features	: -
Housing material	: plastic
Colour	: white
Mounting device	: mounting bracket
Protected against ball rebound	: -
Protection class	: -
Admiss. ambient temp.	: 0-40 °C
Power supply	: &acd; 230 V/50 Hz/110 VA
Dimensions	: 180 x 250 x 160 mm
Width	: 180 mm
Height	: 250 mm
Depth	: 160 mm
Weight	: 5.9Â kg (pair)



Inputs	: 1 x RCA L/R (active speaker system only) 1 x 3.5 mm jack screw terminals (both speaker systems)
Outputs	: -
Replacement voice coil	: -
Other features	: -
Accessories	: -