

ATS-22T - 16 Channel Mini. Transmitter



16-channel Digital Voice Transmission System, 863-865 MHz

- Suitable as a tour guide system, trainer/student system and for any other application in which a certain voice source is to be distributed to one or more receivers
- High resistance to interference due to digital transmission
- Parallel operation of up to 4 different channels possible without any interference
- Licence-free in the EU

16-channel miniature transmitter,
for microphone operation and audio line signals, with intercom function.

- Supplied with headset
- Activation switch for intercom function with the receiver ATS-22R
- Audio line input via 3.5 mm jack at the headset
- LCD for indicating channel and battery status
- Mute button
- Transmitting power: (tm) 10 mW (EIRP), operating range: approx. 70 m
- Power supply via integrated rech. lithium battery (3.7 V/600 mAh)
- Micro USB charging connection for ATS-12CB, ATS-35CB or USB charger, available at option
- Dimensions: 40 x 80 x 12 mm
- Weight: 37 g

Licence-free in the EU.

Tekniske data

General information

| | |
|----------------------------|---|
| Description | : - |
| Carrier frequency range | : 16-channel digital miniature transmitter |
| Audio frequency range | : 863-865 MHz |
| Channels | : - |
| THD | : - |
| Dynamic range | : - |
| RF S/N ratio | : - |
| Operating time | : - |
| Admiss. ambient temp. | : 0-40 °C |
| Power supply | : - |
| Dimensions | : - |
| Total weight | : - |
| Connections | : - |
| Specifications transmitter | : |
| Transmitting power | : ? 10 mW |
| Operating range | : 70 m |
| Power supply transmitter | : integrated rech. lithium batt. (3.7 V/600 mAh) |
| Width transmitter | : 40 mm |
| Height transmitter | : 80 mm |
| Depth transmitter | : 12 mm |
| Weight transmitter | : 37 g |
| Connections transmitter | : 3.5 mm jack (microphone/line in), micro USB charging port |
| Specifications receiver | : - |
| Audio signal receiver | : - |
| Power supply receiver | : - |
| Width receiver | : - |
| Height receiver | : - |
| Depth receiver | : - |
| Weight receiver | : - |
| Connections receiver | : - |