-

Tekniske data

Peak output power	: -
Power rating	: 80 W
Power rating at 2 Ohm	: -
Power rating at 4 Ohm	: -
Power rating at 8 Ohm	: -
Power rating at 16 Ohm	: -
Power rating at 100 V	: -
Power rating with 4 Ohm bridged operation	: -
Power rating with 8 Ohm bridged operation	: -
Output impedance	: -
Channels	: 3
Zones	: -
Inputs	: 1.5Â mV (mic),300 mV (line)
Attenuation factor	: -
Frequency range	: 50-15,000 Hz
Crossover network	: -
Crossover frequency	: -
Integrated limiter	: -
Equalizer bass	: ± 10Â dB/100Â Hz
Equalizer midrange	: -
Equalizer treble	: ± 10Â dB/10Â kHz
S/N ratio	: ? 52 dB
Crosstalk attenuation	: -
THD	: 1%
Mains voltage	: ∼ 230 V
Mains frequency	: 50 Hz
Power consumption, operation	: 265 VA
Power consumption, standby	: -
Standby current	: -
Operating voltage (possible alternative)	: -
Power supply (possible alternative)	: -
Admiss. ambient temp.	: 0-40 °C
Width	: 400 mm
Height	: 110 mm

Depth	: 340 mm

Rack spaces, RS	:	2
Weight	:	9.5 kg
Connections	:	2 x 6.3 mm jack (mic),1 x 6.3 mm jack (mic/line), screw terminals (speakers)