

HSE-150/SK - Headworn Microphone



Ultra-light headband microphone

Suitable for the reproduction of vocals and speech for any kind of audio transmission. A high-quality back electret cartridge with omnidirectional polar pattern provides a good sound of a high quality even if the cartridge is not perfectly aligned. An ergonomic design is the reason for both an unobtrusive and secure fit even during extreme head movements.

- Wide transmission range
- Very comfortable to wear
- Stable positioning
- Turning cartridge arm of adjustable length
- Drip ring (protects cartridge from moisture)
- Compatible with all TXS-...HSE pocket transmitters with 3-pole mini XLR connection
- External power supply e.g. via phantom power supply adapter EMA-1 or EMA-300P
- Microphone windshield

Ultra-light headband microphone

- Omnidirectional polar pattern
- High-quality back electret cartridge
- 3-pole mini XLR connection
- Turning cartridge arm of adjustable length
- Drip ring (protects cartridge from moisture)
- Compatible with all TXS-...HSE pocket transmitters with 3-pole mini XLR connection
- External power supply, e.g. via phantom power supply adapter EMA-1 or EMA-300P
- Microphone windshield

tools4music 03/2012

“During the test with well-known reference units, it emerged that a real price-performance tip is now available from the audio distributor in Bremen, Germany: the HSE-150/SK. Conclusion: anyone who wants to invest in new headsets with a good price-performance ratio for every-day use should try out the HSE-150/SK and the earband microphone HSE-70A/SK in a personal test environment.”

- + Comfortable to wear
- + Well-balanced sound tuning
- + Very good price-performance ratio

Tekniske data

Description	: headband microphone
Version	: -
Transmission method	: cable
Polar pattern	: omnidir.
System	: back electret
Carrier frequency range	: -
Transmitting power	: -
Power supply	: -
Operating time	: -
Audio frequency range	: 20-20,000 Hz
Nominal impedance	: 1 kOhm
Sensitivity	: 8 mV/Pa
S/N ratio	: -
Max. sound pressure	: 130 dB
Power supply	: DC 1.5-9 V
Gooseneck length	: -
Housing material	: -
Admiss. ambient temp.	: 0-40 °C
Dimensions	: -
Weight	: 7 g
Cable	: -
Connection	: 3-pole mini XLR