


## DT-75/8 - HiFi Dome Tweeter


FERRO  
FLUID

50  
W<sub>RMS</sub>

25  
Ω



**DT-75/8**



Hi-fi dome tweeter, 25 W, 8 Ohm

- Soft dome
- High-quality reproduction
- Ferrofluid

## Tekniske data

Impedance (Z)	: 8 Ohm
Transmission method	: -
Frequency range	: fx-20,000 Hz
Resonant frequency (fs)	: 2,000 Hz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	: 3,000 Hz
Power rating (RMS)	: 25 W
Peak music power output (MAX)	: 50 W
Sensitivity	: 90 dB/W/m
Max. rated SPL	: -
Max. voltage	: -
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Suspension compl. (Cms)	: -
Moving mass (Mms)	: -
Mech. Q factor (Qms)	: -
Electr. Q factor (Qes)	: -
Total Q factor (Qts)	: -
Equivalent volume (Vas)	: -
DC resistance (Re)	: -
Force factor (BxL)	: -
Voice coil induct. (Le)	: -
Voice coil diameter	: $\varnothing \sim 25$ mm
Voice coil former	: -
Linear excursion ( $X_{MAX}$ )	: -
Eff. cone area (Sd)	: -
Magnet weight	: -
Magnet diameter	: $\varnothing \sim 60$ mm
Mounting cutout	: 62 x 70 mm
Mounting depth	: 28 mm
Mounting hole diameter	: -
Hole spacing X-axis	: -
Hole spacing Y-axis	: -
Dimensions	: 93 x 69 x 28 $\varnothing$ mm
Outside diameter	: -
Width	: 93 mm



Height	: 69 mm
Depth	: 28 mm
Protective class	: -
Admiss. ambient temp.	: 0-40 °C
Weight	: 0.335 kg
Packing unit	: 1
Type of speaker	: -