

IT-32EN - Horn Speaker



Weatherproof horn speakers,
with EN 54-24 certification.

- 100 V line technique
- IP66 tested
- Light grey ABS housing (self-extinguishing, complies with the standard UL 94V-0)
- Cable inlet via high-strength cable gland
- Integrated high-pass filter for optimising the sound and stability
- Supplied with mounting bracket

Tekniske data

| | |
|--------------------------------|--------------------------|
| Active/passive | : passive |
| Transmission method | : 100 V |
| Total output power | : - |
| Power rating (RMS) | : - |
| Total power rating | : 30 W |
| Power rating (RMS) | : 30/15/7.5 W |
| Impedance | : - |
| Frequency range | : 350-10,000 Hz |
| THD | : - |
| S/N ratio | : - |
| Input signal | : - |
| System | : - |
| Full range speaker | : - |
| Bass speaker | : - |
| Midrange speaker | : - |
| Tweeter | : - |
| Number of speakers | : 1 |
| Speaker size | : - |
| Sensitivity | : 110 dB/W/m |
| Max. rated SPL | : - |
| Radiation angle, horizontal | : 110° |
| Radiation angle, vertical | : 55° |
| Features | : EN 54-24 certification |
| Housing material | : ABS, UL 94V-0 |
| Colour | : light grey |
| Mounting device | : mounting bracket |
| Protected against ball rebound | : - |
| Protection class | : IP66 |
| Admiss. ambient temp. | : -25 °C to +70 °C |
| Power supply | : - |
| Dimensions | : 180 x 120 x 230 mm |
| Width | : 180 mm |
| Height | : 120 mm |
| Depth | : 230 mm |
| Weight | : 2.1 kg |



| | |
|------------------------|----------------|
| Inputs | : - |
| Outputs | : - |
| Replacement voice coil | : - |
| Other features | : weatherproof |
| Accessories | : - |