

## IT-32EN - Horn Speaker



Weatherproof horn speakers,  
with EN 54-24 certification.

- 100 V line technique
- IP66 tested
- Light grey ABS housing (self-extinguishing, complies with the standard UL 94V-0)
- Cable inlet via high-strength cable gland
- Integrated high-pass filter for optimising the sound and stability
- Supplied with mounting bracket

## Tekniske data

|                                |                          |
|--------------------------------|--------------------------|
| Active/passive                 | : passive                |
| Transmission method            | : 100 V                  |
| Total output power             | : -                      |
| Power rating (RMS)             | : -                      |
| Total power rating             | : 30 W                   |
| Power rating (RMS)             | : 30/15/7.5 W            |
| Impedance                      | : -                      |
| Frequency range                | : 350-10,000 Hz          |
| THD                            | : -                      |
| S/N ratio                      | : -                      |
| Input signal                   | : -                      |
| System                         | : -                      |
| Full range speaker             | : -                      |
| Bass speaker                   | : -                      |
| Midrange speaker               | : -                      |
| Tweeter                        | : -                      |
| Number of speakers             | : 1                      |
| Speaker size                   | : -                      |
| Sensitivity                    | : 110 dB/W/m             |
| Max. rated SPL                 | : -                      |
| Radiation angle, horizontal    | : 110°                   |
| Radiation angle, vertical      | : 55°                    |
| Features                       | : EN 54-24 certification |
| Housing material               | : ABS, UL 94V-0          |
| Colour                         | : light grey             |
| Mounting device                | : mounting bracket       |
| Protected against ball rebound | : -                      |
| Protection class               | : IP66                   |
| Admiss. ambient temp.          | : -25 °C to +70 °C       |
| Power supply                   | : -                      |
| Dimensions                     | : 180 x 120 x 230 mm     |
| Width                          | : 180 mm                 |
| Height                         | : 120 mm                 |
| Depth                          | : 230 mm                 |
| Weight                         | : 2.1 kg                 |



---

|                        |                |
|------------------------|----------------|
| Inputs                 | : -            |
| Outputs                | : -            |
| Replacement voice coil | : -            |
| Other features         | : weatherproof |
| Accessories            | : -            |