-

Tekniske data

Peak output power	: -
Power rating	: 120 W
Power rating at 2 Ohm	: -
Power rating at 4 Ohm	: -
Power rating at 8 Ohm	: 120 W
Power rating at 16 Ohm	: -
Power rating at 100 V	: 120 W
Power rating with 4 Ohm bridged operation	: -
Power rating with 8 Ohm bridged operation	: -
Output impedance	: -
Channels	: 1
Zones	: -
Inputs	: 1 V/10Â kOhm, bal.
Attenuation factor	: -
Frequency range	: 35-18,000 Hz
Crossover network	: -
Crossover frequency	: -
Integrated limiter	: -
Equalizer bass	: -
Equalizer midrange	: -
Equalizer treble	: -
S/N ratio	: ? 86 dB
Crosstalk attenuation	: ? 80 dB
THD	: < 1%
Mains voltage	: ∼ 230 V
Mains frequency	: 50 Hz
Power consumption, operation	: 320 W
Power consumption, standby	: -
Standby current	: 0.16 A
Operating voltage (possible alternative)	: DC 24 V
Power supply (possible alternative)	: DC 7.5 A
Admiss. ambient temp.	: 0-40 °C
Width	: 425 mm
Height	: 88 mm
Depth	: 305 mm

Rack spaces, RS	:	2
Weight	:	8.5 kg
Connections	:	XLR/screw terminals (input), screw terminals (speakers)