

PA-1200 - PA Amplifier



4-zone mono PA mixing amplifier

- 1 x 120 W
- Silent operation due to fanless cooling concept
- Chime, continuous sound and wailing sound, automatic mute, chime can also be activated via external momentary push-button, 2-tone chime or 4-tone chime (selectable)
- Bass, treble and master controls, level display via LEDs
- 15 V phantom power for channels 2 and 3
- Insertions for various functions are available at option
- 482 mm (19") rack installation with mounting frame PA-1200RM, available at option
- Mains operation and 24 V emergency power operation

Tekniske data

Peak output power	: 170 W
Power rating	: 120 W
Power rating at 2 Ohm	: -
Power rating at 4 Ohm	: -
Power rating at 8 Ohm	: -
Power rating at 16 Ohm	: -
Power rating at 100 V	: -
Power rating with 4 Ohm	: -
bridged operation	
Power rating with 8 Ohm	: -
bridged operation	
Output impedance	: -
Channels	: 5
Zones	: 4
Inputs	: 1.5 mV/600 Ohm (mic), 150 mV/47 kOhm (line), 1 mV/47 kOhm (phono)
Attenuation factor	: -
Frequency range	: 80-15,000 Hz
Crossover network	: -
Crossover frequency	: -
Integrated limiter	: -
Equalizer bass	: ± 10 dB/100 Hz
Equalizer midrange	: -
Equalizer treble	: ± 10 dB/10 kHz
S/N ratio	: ? 60 dB (mic), ? 70 dB (line)
Crosstalk attenuation	: -
THD	: < 1%
Mains voltage	: \sim 230 V
Mains frequency	: 50 Hz
Power consumption, operation	: 280 VA
Power consumption, standby	: -
Standby current	: -
Operating voltage (possible alternative)	: DC 24 V
Power supply (possible alternative)	: DC 11 A
Admiss. ambient temp.	: 0-40 °C

Width : 420 mm
Height : 122 mm
Depth : 350 mm





Rack spaces, RS	: -
Weight	: 12.28 kg
Connections	: 1 x 6.3 mm jack (mic input), 3 x XLR, bal. (mic/line inputs), 1 x RCA L + R (line input), 1 x RCA L + R (phono/line input), 1 x twin spring-loaded terminal (telephone input), 1 x twin spring-loaded terminal (tuner output), 1 x twin spri